

SUPABORD - STANDARD TEMPORARY FLOOR PROTECTION SPECIFICATION SHEET



DESCRIPTION

SupaBord Standard is our medium duty temporary floor protection product for residential construction and renovation projects.

SupaBord Standard is the latest technology in floor protection that is light weight but provides a balance of vapour permeability, durability and strength. Developed to withstand the demands of residential renovations, SupaBord Standard has low impact resistance and robust against light wheeled traffic. With each roll conveniently sized at approximately 800mm wide x 33m long x 0.5mm thick, covering 26.5sqm, SupaBord Standard is flexible yet strong and made from 100% recycled material. SupaBord Standard is versatile as it can be scored and folded easily to protect surfaces, making it ideal for benchtops and stairs.

SupaBord Standard prevents the risk of damage and rework, saving money on material and labour costs and is the brand of choice by contractors worldwide.

FEATURES



SPILL RESIST



QUICK FIT



BREATHABLE



MEDIUM DUTY



100% RECYCLED



CUT & FOLD

INSTALLATION INSTRUCTIONS

1. Ensure the subfloor (base floor) is **clean and dry**
2. Remove plastic sleeve from the **SupaBord** roll
3. Roll out **SupaBord** over the flooring area or surface, logo side facing up
4. Cut **SupaBord** to length with a utility knife, ensuring the seams are neat and fit well together
5. Tape the **SupaBord** butt joints, long joints and perimeter with **SupaBord Joint Tape**. **Do not apply SupaBord Joint Tape to floor surfaces as it may affect some finishes**
6. Apply **SupaBord Edge Tape** to the outside perimeter of the flooring area

SupaBord

Bord Industries HK Ltd

Suite 1106-8, 11/F, Tai Yau Building,

181 Johnston Road, Wanchai, Hong Kong

technical@supabord.com www.supabord.com



SUPABORD - STANDARD TEMPORARY FLOOR PROTECTION MATERIAL SAFETY DATA SHEET



PRODUCT & COMPANY IDENTIFICATION

Distributor Name:

Bord Industries HK Ltd
Suite 1106-8, 11/F, Tai Yau Building,
181 Johnston Road, Wanchai, Hong Kong

Product information contact:

technical@supabord.com

MSDS information contact:

technical@supabord.com

Product name:

SupaBord Standard
Temporary Floor Protection

Issue Date: June 2016**Product description:**

Gypsum liner paper and various chip
board - 100% recycled

PRODUCT SPECIFICATIONS

Thickness:	0.5mm (approx.)
Density:	3.26 - 3.31
Mullen Burst:	140 p.s.i.
Taber Stiffness MD:	1703.7 gf/cm
Taber Stiffness CD:	647.6 gf/cm
Caliper	
Low Spec:	44.01
Target Spec:	45.03
High Spec:	46.02
Basis Weight	
Low Spec:	140.90
Target Spec:	143.97
High Spec:	147.05
Moisture	
Low Spec:	4.05%
Target Spec:	6.00%
High Spec:	7.50%

AVAILABLE SIZE

Colour: Natural

Roll Size: Approximately 800mm wide x 33m long x 0.5mm thick, covers 26.5sqm

Roll Weight: Approximately 10kg (22.05lbs)

HANDLING AND STORAGE

No special handling requirements. Keep away from flammable and combustible material. Paper products will not release hazardous chemicals under normal conditions of use.

USES

SupaBord Standard provides ideal protection when painting, plastering or simply preventing mud, dirt and dust from being walked on to the floor. It provides excellent protection for counter tops, cabinets and stairs.

SAFETY

Upon review of relevant OSHA regulations and the characteristics of paperboard, a MSDS is not required because paperboard falls within the exemptions for a 'manufactured article' and 'wood products'.

DISCLAIMER

Reasonable care has been taken in preparation of this document. The information in this document was obtained from sources, which we believe reliable. Bord Industries HK Ltd extends no warranties and makes no representations as to the expressed or implied accuracy or completeness of the information contained therein. We do not assume or accept responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. We disclaim all liability for any harmful health effects, which may be caused by misuse of our products.

