15mm | Herringbone Flooring (AB Grade)

OORING AUSTRALIA



PRODUCT SPECIFICATION DATA SHEET

Timber Species Grade	European Oak AB
Construction	Multi Layer Cross Plywood
Board Dimensions	600mm (Length) x 120mm (Width)
Thickness Top Layer	15mm 3mm Veneer
Surface Finish	Brushed UV Lacquer Matte Finish
Joining System	Tongue + Groove
Edging	4 Sided Micro-Bevel
Installation Method	Direct Glue Down
Pack Size	1.152 m² 16 x Boards 10.5kgs
Slip Test Rating	Р3
Fire Report Rating	CHF Value: 3.7 kW/m2 Smoke Value: 64 %.min
Warranty	Residential: 20 Years Commercial: On Request

commitment to quality, innovation, and customer satisfaction makes them the perfect choice for transforming your space into a haven of luxury and style. Embrace the beauty of engineered timber flooring and let your floors tell a story of elegance and sophistication.

AB GRADE:

This is the highest grade available in engineered timber flooring. This wood is cut from the centre of the tree, and the wood from the centre is much more uniform and has far less knots & imperfections. AB grade flooring is hand selected, offering a premium grade of engineered timber flooring.





WHISPER OAK







TUDOR OAK